ECOREEL 16 THT

The ECOREEL 16 THT is fully enclosed electric boom reel, incorporating everything needed to deploy up to 600 metres of self-expanding boom quickly and safely.

ECOREEL 16 THT

Product	
ECOREEL	16 THT
Construction	Corrosion protected carbon steel to Norsok M-501 offshore specifications
Drum diameter [mm]	2100
Net volume [m3]	16
Brake	Parking brake + hydraulic brake valve
Max traction [kgf] (full load)	1350
Max traction [kgf] (unloaded)	4650
Power supply	15 kW
Operating speed	0-12 rpm, depending on flow rate
Length [mm]	6056
Width [mm]	2460
Height [mm] with hard top	3561
Tare [kg] without/with hard top	6100 / 8500
M.G.W [mm]	13500

The hard shell is fitted with roll-up doors, protecting the equipment from the elements, UV light and vandalism. To operate the unit, only an electrical connection is required, making it immediately usable without the need for an external generator or hydraulic hoses.

Operation is by radio remote control, allowing personnel to remain at a safe distance while maintaining full control over the reel.

The ECOREEL makes it possible to retrieve the boom without being physically in contact with it, as the boom is automatically distributed on the drum while the reel slowly swings back and forth on its rotating base.

The ECOREEL 16 THT, with its proven and patented design, is corrosion protected to offshore specifications (Norsok M-501) for long product durability and minimal maintenance in marine environments.

Contact

Markleen Management S.L. Address: Río Gállego, C/ E, 22, 50840 San Mateo de Gállego, Zaragoza, Spain • Email:markleen@markleen.eu • Telephone (+34) 976 68 30 00.